

Description

The SMIRF20N65T2TL can be used in various power swithching circuit for system miniaturization and higher efficiency. The package form is TO-220/TO-220F, which accords with the RoHS standard.

G D S

General Features

 $V_{DS} = 650V, I_D = 20A$ $R_{DS(ON)} < 0.3 \Omega@V_{GS} = 10V$

TO-220F

N-Channel MOSFET

Application

• Power switch circuit of adaptor and charger.

Package Marking and Ordering Information

Product ID	Pack	Marking	Units Tube
SMIRF20N65T2TL	TO-220F	20N65 XXX YYYY	50

Absolute Maximum Ratings@T=25°C(unless otherwise specified)

Symbol	Parameter	Limit	Unit	
V _{DSS}	Drain-to-Source Voltage ^[1]	650		
V _{GSS}	Gate-to-Source Voltage	±30		
I _D	Continuous Drain Current	20		
I _{D @ Tc =100°C}	Continuous Drain Current @ Tc=100°C 13		Α	
I _{DM}	Pulsed Drain Current at V _{GS} =10V ^[2]	80		
E _{AS}	Single Pulse Avalanche Energy	980	mJ	
P _D	Power Dissipation	32	W	
T _L T _{PAK}	Maximum Temperature for Soldering Leads at 0.063in (1.6mm) from Case for 10 seconds, Package Body for 10 seconds	300 260	°C	
T _J & T _{STG}	Operating and Storage Temperature Range	-55 to 150		
R _{θJC}	Thermal Resistance, Junction-to-Case	3.9	°C AA/	
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	55	°C/W	

Caution: Stresses greater than those listed in the "Absolute Maximum Ratings" may cause permanent damage to the device.

Electrical Characteristics T_J =25 ℃ unless otherwise specified

Symbol	Parameter	Conditions	Min.	Тур.	Max.	Unit
V _{(BR)DSS}	Drain-Source Breakdown Voltage	$I_D = 250 \mu A, V_{GS} = 0 V$	650	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 650V, V_{GS} = 0V$	-	-	1.0	μА
I _{GSS}	Gate-Body Leakage Current	$V_{DS} = 0V, V_{GS} = \pm 30V$	-	-	±100	nA
V _{GS(th)}	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_{D} = 250 \mu A$	2	3	4	V
R _{DS(ON)}	Static Drain-Source ON-Resistance ⁽⁴⁾	$V_{GS} = 10V, I_D = 10A$	-	0.4	0.47	Ω
C _{iss}	Input Capacitance)/ 01/1/ 05\/	-	3234	-	pF
C _{oss}	Output Capacitance	$V_{GS} = 0V$, $V_{DS} = 25V$, $f = 1MHz$	-	266	-	pF
C _{rss}	Reverse Transfer Capacitance	1 - 11/11/12	-	34	-	pF
Q_g	Total Gate Charge	$V_{GS} = 0 \text{ to } 10V$ $V_{DS} = 520V, I_{D} = 20A$	-	73	-	nC
Q_{gs}	Gate Source Charge		-	17	-	nC
Q_{gd}	Gate Drain("Miller") Charge	V _{DS} = 626 V, I _D = 267 V	-	29	-	nC
t _{d(on)}	Turn-On DelayTime		-	45	-	ns
t _r	Turn-On Rise Time	$V_{GS} = 10V, V_{DD} = 330V$ $I_{D} = 20A, R_{GEN} = 24\Omega$	-	64	-	ns
t _{d(off)}	Turn-Off DelayTime		-	218	-	ns
t _f	Turn-Off Fall Time		-	84	-	ns
I _S	Maximum Continuous Drain to Source Diode Forward Current		-	-	20	Α
I _{SM}	Maximum Pulsed Drain to Source Diode Forward Current		-	-	80	Α
V _{SD}	Drain to Source Diode Forward Voltage	$V_{GS} = 0V, I_{S} = 20A$	-	-	1.2	V
trr	Body Diode Reverse Recovery Time	1 004 11/14 4004/	-	494	-	ns
Qrr	Body Diode Reverse Recovery Charge	I _F = 20A, di/dt = 100A/us	-	7.9	-	μC

Notes: 1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.

^{2.} E_{AS} condition: Starting T_J =25C, V_{DD} =50V, V_G =10V, R_G =25ohm, L=10mH, I_{AS} =14A

^{3.} $R_{\theta JA}$ is measured with the device mounted on a minimum recommended pad of 2oz copper FR4 PCB

^{4.} Pulse Test: Pulse Width≤300µs, Duty Cycle≤0.5%.



Typical Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 4: Body Diode Characteristics




Figure 5: Gate Charge Characteristics




Figure 6: Capacitance Characteristics






Figure 7: Normalized Breakdown voltage vs.
Junction Temperature




Figure 9: Maximum Safe Operating Area




Figure 11: Normalized Maximum Transient Thermal Impedance




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 10: Maximum Continuous Drian Current vs. Case Temperature





Figure 12: Peak Current Capacity



Test Circuit




Figure 1: Gate Charge Test Circuit & Waveform




Figure 2: Resistive Switching Test Circuit & Waveform




Figure 3: Unclamped Inductive Switching Test Circuit& Waveform





Figure 4: Diode Recovery Test Circuit & Waveform



Package Dimension TO-220F



Symbol	Dimensions In Millimeters		Dimensions In Inches			
	Min.	Max.	Min.	Max.		
Α	4.300	4.700	0.169	0.185		
A1	1.300	1.300 REF.		0.051 REF.		
A2	2.800	3.200	0.110	0.126		
A3	2.500	2.900	0.098	0.114		
b	0.500	0.750	0.020	0.030		
b1	1.100	1.350	0.043	0.053		
b2	1.500	1.750	0.059	0.069		
С	0.500	0.750	0.020	0.030		
D	9.960	10.360	0.392	0.408		
E	14.800	15.200	0.583	0.598		
е	2.540	2.540 TYP. 0.100 TYF		TYP.		
F	2.700 REF.		0.106 REF.			
Φ	3.500	REF.	0.138 REF.			
h	0.000	0.300	0.000	0.012		
h1	0.800 REF.		0.031 REF.			
h2	0.500 REF.		0.020 REF.			
L	28.000	28.400	1.102	1.118		
L1	1.700	1.900	0.067	0.075		
L2	1.900	2.100	0.075	0.083		



Attention

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.
- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.
- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production.

 HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.