




Description:

The ULN2803ADWR device is a 50 V, 500 mA Darlington transistor array.

The device consists of eight NPN Darlington pairs that feature high-voltage outputs with common-cathode clamp diodes for switching inductive loads.

The collector-current rating of each Darlington pair is 500 mA. The Darlington pairs may be connected in parallel for higher current capability.

Applications include relay drivers, hammer drivers, lamp drivers, display drivers (LED and gas discharge), line drivers, and logic buffers. The ULN2803ADWR device has a 2.7-k Ω series base resistor for each Darlington pair for operation directly with TTL or 5-V CMOS devices.




Pin 1

SOP-18


Features:

- 500-mA-Rated Collector Current (Single Output)
- High-Voltage Outputs: 50 V
- Output Clamp Diodes
- Inputs Compatible With Various Types of Logic

Logic Diagram



Pin Configuration and Functions





Absolute Maximum Ratings (T A = 25°C and rating apply to any one device in the package, unless otherwise noted.)


Characteristics	Symbol	Parameter		Unit
		Min	Max	
Collector-emitter voltage	VCE	-	50	V
Input voltage	Vi		30	V
Collector current- continuous	Ic	-	500	mA
Base current- continuous	IB		25	mA
Junction temperature	Tj		125	°C
Operating temperature	Tamb	-20	80	°C
Storage temperature	Tstg	-55	150	°C

Electrical Characteristics (unless otherwise specified: T A =25°C)



Characteristics	Test conditions	Symbol	Parameter			Unit
			Min	Typ	Max	
Output leakage current	Vo=50V, Tamb= +85°C	ICEX			100	μA
	Vo=50V, Tamb= +25°C				50	μA
Collector-Emitter saturation voltage	Ic=350mA, IB=500μA	VCEs		1.5	1.7	V
	Ic=200mA, IB=350μA			1.15	1.3	V
	Ic=100mA, IB=250μA			0.85	1.1	V
Input current - on condition	VI=3.85V	II (ON)		1.15	1.35	mA
Input voltage - on condition	VCE=2.0V, Ic=200mA	VI (ON)			2.4	V
	VCE=2.0V, Ic=250mA				2.7	
	VCE=2.0V, Ic=300mA				3.0	
Input current - off condition	VCE=2.0V, Ic=300mA	II (OFF)	50	100		μA
Input capacitance		CI		15	30	pF
Turn-on delay time (50% EI to 50% EO)	50%EI to 50%Eo	tON		0.25	1	μs
Turn-off delay time (50% EI to 50% EO)	50%EI to 50%Eo	tOFF		0.25	1	μs
Clamp diode leakage current (VR=50V)	VR=50V	Tamb= +25°C	IR		50	μA
		Tamb= +85°C			100	
Clamp diode forward Voltage	IF=350mA	VF		1.5	2	V



Typical Application:



Typical Characteristics:






Outline Drawing

SOP-18

Unit:mm





Attention

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.
- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.
- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.